


**USPTM PT 20** was designed for use in light commercial and industrial applications. PT 20 is ideal for private parks and schools, warehouses, auto dealerships/parking lots, sports facilities and a wide variety of other applications. It is also ideal for industrial gate framework.


**Superior Corrosion Resistance** - With our advanced coating process, US Premier Tube Mills guarantees the highest degree of corrosion resistance available. PT 20 features the identical triple layer coating process of our PT 40. A triple layer of OD corrosion protection consisting of a zinc bath, an intermediate conversion coat and a clear vacuum sealed top coat is then added to provide the maximum in protection and durability. The ID is zinc coated prior to forming.

**Strength** - PT 20 is fabricated to conform to ASTM A 653 with a high yield strength of 50,000 PSI. And because its yield strength is 65% greater and 20% lighter than hot dip galvanized pipe, it is ideal for gate framework.

Made in U.S.A. - All PT 20 product from USPTM is manufactured in the USA and is in compliance with federal, state, and local specifications. Available in Polyester and heavy mil Polyolefin Color Coat. We are a domestic manufacturer of domestic steel products made from only domestic steel sources.







		Outside	Pipe Wall	Weight	Section	Yield	Bending	Bending	Bundle Counts
Posts		Dimensions (in.)	Thickness (in.)	(lbs./ft)	<b>Modulus</b> (inches <sup>3</sup> )	Strength (psi)	Moment (Ibs. in.)	Strength (lbs.) 6' Cantilever Load	(pcs.)
1- <sup>7</sup> /8" O.D.	<b>PT 20</b> SG	<b>1.900</b> 1.900	<b>.090</b> .116	1.74 2.21	<b>0.2212</b> 0.2735	<b>50,000</b> 25,000	<b>11,060</b> 6,835	<b>154</b> 95	61
2- <sup>3</sup> /8" O.D.	<b>PT 20</b> SG	<b>2.375</b> 2.375	<b>.095</b> .116	<b>2.32</b> 2.80	<b>0.3731</b> 0.4434	<b>50,000</b> 25,000	<b>18,655</b> 11,085	<b>259</b> 154	37
2- <sup>7</sup> /8" O.D.	<b>PT 20</b> SG	<b>2.875</b> 2.875	<b>.110</b> .128	<b>3.25</b> 3.76	<b>0.6364</b> 0.7264	<b>50,000</b> 25,000	<b>31,820</b> 18,160	<b>442</b> 252	19
Top Rail								10' Supported	
1- <sup>3</sup> /8" O.D.	<b>PT 20</b> SG	1.315 1.315	<b>0.080</b> 0.116	<b>1.06</b> 1.49	<b>0.0904</b> 1.2050	<b>50,000</b> 25,000	<b>4,519</b> 3,013	<b>151</b> 100	91
1- <sup>5</sup> /8" O.D.	<b>PT 20</b> SG	<b>1.660</b>	.085 .116	1.43 1.91	<b>0.1576</b> 0.2032	<b>50,000</b> 25,000	<b>7,880</b> 5,079	<b>263</b> 169	61

YOUR SOURCE FOR QUALITY STEEL FENCE PIPE AND TUBING

US Premier Tube Mills | 2855 Michigan Road, Madison, IN 47250 | P: 812.265.7001 | F: 812.274.0345 | contact@USPTmills.com USPTMILLS.COM



